



ROO GASBAGS

Australasian Mining Services
www.austms.com

ROO gasbags are specially designed 2-speed aerosol inflated blast-hole plugs that can be activated and dropped down dry production blast holes for faster decking.

The reliability of ROO gasbags is assured using a patented total release actuator which comes with a 2-speed option. Once the total release actuator is activated, the gas impermeable multi layered bag inside the robust woven outer sleeve is inflated with non-flammable gas released from the aerosol canister.

The ROO gasbags are classified by the National Industrial Chemical Notification and Assessment Scheme (NICNAS) as a non-flammable gas and classified under the Australian Dangerous Goods Code as a Class 2, Division 2.2 nonflammable and nontoxic gas.

ROO gasbags are 11% longer than competitor gas bags, resulting in a larger contact surface area with increased stability and hold of the gas bag once inflated.

The product is designed to hold up to 1.7MPa without significant shape change. Additional features include a break-away tab and the use of expansion-retaining wrap keeping the gasbag in tubular form for easy positioning

ADVANTAGES

- Fast and easy to install
- 2-speed option
- Non-flammable gas
- 11% added length
- Larger contact surface area
- Enhanced box packaging with handle



Product Code	Blast Hole Size (mm)		Box Qty
	From	To	
ROO115-127HFC	115	127	30
ROO150-165HFC	150	165	30
ROO200-230HFC	200	230	25
ROO250-270HFC	250	270	25
ROO311HFC	311	311	25